



THERMAL PROCESSING
TRAINING

Module 12. Hydrostatic Retorts

9 CFR 431.6(b)(5) Hydrostatic Retorts



Purpose and Objectives



THERMAL PROCESSING TRAINING


- Purpose of Module 12
 - Provide an understanding of components and operation of equipment used for hydrostatic retorts.
- Performance Objective
 - Assess compliance of hydrostatic retort equipment and perform inspections



Hydrostatic Retort



THERMAL PROCESSING
TRAINING




Introduction



THERMAL PROCESSING TRAINING

- Constant process temperature
- Continuous container conveyor
- Steam or cascading water with overpressure




Processing Chamber Pressure



THERMAL PROCESSING TRAINING

- Hydrostatic pressure of water columns counterbalance steam pressure
- Maximum process temperature limited by maximum height of legs



Description of System



THERMAL PROCESSING
TRAINING

Container-Conveyor:

- Carriers for holding containers
- Carriers limit container sizes
- Multiple container-conveyors



Feed and Discharge Stations



THERMAL PROCESSING
TRAINING


A variety of mechanisms are used to load and unload containers from conveyor.



Feed and Discharge Stations (2)



THERMAL PROCESSING
TRAINING



In-Feed Section



THERMAL PROCESSING TRAINING

- Extends from feed station to entry into first water column
- Section may be covered



Feed or Inlet Leg



THERMAL PROCESSING TRAINING

- Water column(s) prior to entry into processing chamber
- Independent temperature control
- Steam injection at base




Processing Chamber (Steam Dome)



THERMAL PROCESSING TRAINING

- Temperature control independent of water legs
- In steam retorts referred to as "steam dome"



Discharge or Exit Leg



THERMAL PROCESSING
TRAINING

- Water column(s) prior to return to atmospheric pressure
- Independent temperature control



Discharge Leg Temperature



THERMAL PROCESSING
TRAINING


- Steam injection to heat
- Maintained by container heat (primary)
- Cross-circulation between legs (usually done)
- Heat exchanger to cool leg if more rapid cooling is desired



Water Circulation and Temperature Control



THERMAL PROCESSING
TRAINING



Container Cooling



THERMAL PROCESSING
TRAINING

- Cascading water
- Water sprays





**THERMAL PROCESSING
TRAINING**

Installation and Operation of Retorts





Temperature Indicating Device

- Each processing chamber **must** have temperature indicating device and temperature/time recorder
- **Must** be installed near steam-water interface 3 inches above maximum water level



Water Leg Temperature



THERMAL PROCESSING
TRAINING

When minimum temperature in the water legs is specified in process schedule there **must** be:

1. Temperature indicating device
2. Temperature/ time recorder




Temperature/Time Recorder



THERMAL PROCESSING TRAINING

- Bulb must be installed in processing chamber
- Between steam-water interface and lowest container position



Steam Controller



THERMAL PROCESSING
TRAINING

- **Must** have an automatic steam controller
- May be recorder-controller



Preparation for Processing



THERMAL PROCESSING
TRAINING

- Operating procedures **must** be documented by manufacturer or processing authority
- Steam dome **must** be vented – The firm should refer to the equipment manufacturers' instructions for venting or have a written vent schedule from their Process Authority



Bleeders



THERMAL PROCESSING
TRAINING

Bleeders **must** be:

- 1/4-inch or larger opening
- Located opposite steam entry
- Wide open during processing
- Arranged to observe functioning



Water Level Control



THERMAL PROCESSING
TRAINING

- Level defines conveyor length in processing chamber(s) or steam dome
- Level affected by height of water legs and processing chamber temperature/pressure
- Called steam-water interface



Water Level



THERMAL PROCESSING
TRAINING

Water Level:

- Maximum level established by manufacturer

Water level fluctuations:

- Affect process time
- Caused by containers entering and leaving water legs
- Level controlled by system that adds and removes water to the legs



Process Timing



THERMAL PROCESSING
TRAINING

- Container-conveyor is driven by variable speed motor
- Changing container-conveyor speed changes process time



Container Conveyor Speed



THERMAL PROCESSING
TRAINING

The Container Conveyor Speed **must:**

- Be checked and recorded at start of processing and must be checked and recorded at intervals not to exceed 4 hours to ensure correct chain speed
- Provide means to prevent unauthorized changes



Processing Considerations



THERMAL PROCESSING
TRAINING

Feed and Discharge Legs

- Time in heated water legs may be included in scheduled process
- May reduce process time



Water Leg Temperature



THERMAL PROCESSING
TRAINING

If the water leg is included in process schedule, the temperature must be above specified temperature.



Water Level Fluctuation



THERMAL PROCESSING
TRAINING

- Process time shortened if above maximum level
- Automatic device (high water sensor) should stop container-conveyor



Water Level Fluctuation (2)



THERMAL PROCESSING
TRAINING

Water contacting containers in bottom loops:

- May result in underprocessing
- Containers **must** be segregated
- Processing authority evaluation
- Numbered carriers/diagram



Initial Temperature



THERMAL PROCESSING TRAINING

- Measure using method and frequency in the establishment's written procedure
- Feed leg temperature must be considered



Record Requirements



THERMAL PROCESSING
TRAINING

- Critical factors must be measured and recorded in accordance with the method and frequency in the written procedure
- Records **must** include conveyor (chain) speed



Key Points



THERMAL PROCESSING TRAINING

- Hydrostatic retorts use water columns to counterbalance the pressure in the steam dome
- Each retort must be equipped with at least one MIG and time-temperature recording device, in the steam dome as well as in the water legs, if applicable
- The water level in the base of the steam dome must be controlled below the maximum to prevent process deviations
- Process time is dependent on the length of the conveyor chain and the speed of the chain



Questions?



THERMAL PROCESSING
TRAINING

Questions?

